




Publisher homepage: www.universepg.com, ISSN: 2707-4625 (Online) & 2707-4617 (Print)

<https://doi.org/10.34104/ijmms.020.029038>

International Journal of Material and Mathematical Sciences

Journal homepage: www.universepg.com/journal/ijmms



MHD Free Convective Heat Transfer in a Triangular Enclosure Filled with Copper-Water Nanofluid

Tarikul Islam^{1*}, Nahida Akter², and Nusrat Jahan³

^{1&2}Department of Mathematics, Bangabandhu Sheikh Mujibur Rahman Science and Technology University, Gopalganj, Bangladesh; ³Department of Science and Humanity, Bangladesh Army International University of Science and Technology, Cumilla, Bangladesh.

*Correspondence: tarikulamath@gmail.com

ABSTRACT

Two-dimensional time independent free convective flow and temperature flow into a right-angled triangle shape cavity charged by $Cu - H_2O$ nanofluid has been performed. The horizontal side of the enclosure is warmed uniformly $T = T_h$ whilst the standing wall is cooled at low temperature $T = T_c$ and hypotenuse of the triangular is insulated. The dimensionless non-linear governing PDEs have been solved numerically employing the robust PDE solver the Galerkin weighted residual finite element technique. An excellent agreement is founded between the previous, and present studies. The outcomes are displayed through streamline contours, isotherm contours, and local and average Nusselt number for buoyancy-driven parameter Rayleigh number, Hartmann number, and nanoparticles volume fraction. The outcomes show that the temperature flow value significantly changes for the increases of Rayleigh number, Hartmann number, and nanoparticles volume fraction. Average Nusselt number is increased for the composition of nanoparticles whereas diminishes with the increase of Hartmann number.

Keywords: Nanoparticles, MHD, Heat transfer, Finite element method, Free convection, and Triangular cavity.

INTRODUCTION:

Temperature transfer and fluid flow of nanofluids into the triangle shape enclosure have a wide applications in numerous industrial and engineering systems like heat exchangers, fire prevention, solar collectors, home ventilation systems, and refrigeration units etc. Cu -water, Al_2O_3 -water, and TiO_2 -water are very common nanofluids. These nanofluids are used widely for the augmentation of temperature transfer. Enhancement of warmed-up conductivity into nanofluids was studied by Choi and Eastman (1995). Manca *et al.* (2010) performed heat transfer in nanofluids. Influence of external magnetic field on natural convective flow into rectangle shape enclosure

using warmed up and cooled neighbor walls was investigated by Ece and Buyuk (2006). Convective temperature disposal within a cavity heated partially was performed by Ozotop and Abu-Nada (2008). Free convective temperature flow value into nanofluids within an inclined was performed by Ghasemi and Aminossadati (2009). Impact of inclined angle using copper-water nanofluids within an enclosure was investigated Abu-Nada *et al.* (2009). Varol *et al.* (2007) investigated free convective flow within a triangle shape cavity using isothermal heater. Numerical computations of FEM on convective temperature flow into nanofluids within a rectangle shape enclosure was performed by Rahman *et al.*

(2009). FEM numerical computations on free convection into nanofluids within a triangle shape cavity in account of both uniform and non-uniform warmed boundary condition was investigated by Basak *et al.* (2008). A comprehensive review on convectonal flow was researched Kamiyo *et al.* (2010). Aydin and Yesiloz (2011) investigated usual convectonal flow into a quadrantal enclosure using warmed and cooled neighbor walls.

Magnetic field which creates an external force on the thermal and energy systems that highly attack the liquid flow and temperature flowing. Sheikholeslami *et al.* (2014) researched about CuO-water nanofluid effect on convectonal flow taking into account Lorentz force in flow domain. Computational study using Al_2O_3 -water nanofluids on natural convectonal flow was investigated by Rashmi *et al.* (2011). Bhardwaj and Dalal (2013) investigated convectonal temperature flow as well as entropy generation into a right-angled shape triangle cavity. Natural convectonal flow into a nanofluid using horizontal warmed plate was studied by Arani *et al.* (2011). Combined convectonal flow and temperature flow characteristics into lid-driven square enclosure using heated blocks was investigated by Boulahia *et al.* (2016). Magneto hydro dynamics free convectonal temperature transfer into nanofluid within isosceles triangle shape cavity was performed by Rahman *et al.* (2016). Convectonal temperature flow into nanofluid within a triangular shape cavity was performed by Uddin *et al.* (2018).

From the literature review, the principle intention is to investigate the temperature flow and fluid flow within a right-angled triangle shape cavity charged by copper-water nanofluid. The impact of Rayleigh number, volume fraction of nanoparticles and Hartmann number are performed numerically and discussed them from physical point of view.

FORMULATION OF PROBLEM:

Physical Model:

For present study, schematic spectacle for right-angled triangular enclosure has been presented in Fig 1. The length of vertical and horizontal wall of the enclosure is L . The vertical side of enclosure is heated at a low

heat $T = T_c$, whilst its horizontal side is heated at temperature $T = T_h$, ($T_c < T_h$), and the inclined wall is insulated. The enclosure charged as water (H_2O) for base fluid and copper (Cu) for nanoparticles. The gravitational acceleration g acts in downward approach towards y -axis and a uniformly external magnetic field including power (B_0) is also imposed towards horizontal approach. The nanofluid is calculated as incompressible and laminar. Two dimensional time independent flow is processed for current study (Islam *et al.*, 2020). The characteristics of nanoparticles and base fluid is given in Table 1. All solid boundaries are announced as no slip walls.




Fig 1: Schematic spectacle of right-angled triangular enclosure.

Table 1: Thermo-physical characteristics of the base fluid and solid particles.

Physical properties	Copper (Cu)	Water (H ₂ O)
c_p [Jkg ⁻¹ K ⁻¹]	385	4179
ρ [kgm ⁻³]	8933	997.1
k [Wm ⁻¹ K ⁻¹]	400	0.613
μ [kgm ⁻¹ s ⁻¹]	-	0.001003
$\beta \times 10^{-5}$ [K ⁻¹]	1.67	21
σ [Sm ⁻¹]	5.96×10^7	5.5×10^{-6}
Pr	-	6.8377

Mathematical Model:

The governing equations under aforementioned assumption in Cartesian co-ordinate system as follows:

$$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} = 0 \tag{1}$$

$$u \frac{\partial u}{\partial x} + v \frac{\partial u}{\partial y} = -\frac{1}{\rho_{nf}} \frac{\partial p}{\partial x} + \frac{\mu_{nf}}{\rho_{nf}} \left(\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} \right) \tag{2}$$

$$\rho_{nf} \left(u \frac{\partial v}{\partial x} + v \frac{\partial v}{\partial y} \right) = -\frac{\partial p}{\partial y} + \mu_{nf} \left(\frac{\partial^2 v}{\partial x^2} + \frac{\partial^2 v}{\partial y^2} \right) + (\rho\beta)_{nf} g(T - T_c) - \sigma B_0^2 v \tag{3}$$

$$u \frac{\partial T}{\partial x} + v \frac{\partial T}{\partial y} = \alpha_{nf} \left(\frac{\partial^2 T}{\partial x^2} + \frac{\partial^2 T}{\partial y^2} \right) \tag{4}$$

Boundary conditions:

on horizontal wall: $u = 0, v = 0, T = T_h$ (5a)

on perpendicular wall: $u = 0, v = 0, T = T_c$ (5b)

on inclined wall: $u = 0, v = 0, \frac{\partial T}{\partial x} = 0$ (5c)

Dimensional Analysis:

The dimensionless variables are listed below:

$$\left. \begin{aligned} X &= \frac{x}{L}, U = \frac{uL}{\alpha_{bf}}, \theta = \frac{T - T_c}{T_h - T_c}, P = \frac{\rho L^2}{\rho_{nf} \alpha_{bf}^2} \\ Y &= \frac{y}{L}, V = \frac{vL}{\alpha_{bf}}, Ha = B_0 L \sqrt{\sigma_{bf} / \mu_{bf}}, \\ Pr &= \frac{\nu_{bf}}{\alpha_{bf}}, Ra = \frac{g \beta_{bf} (T_h - T_c) L^3}{\nu_{bf} \alpha_{bf}} \end{aligned} \right\} \tag{6}$$

Using the dimensionless variables in equations (1)-(4), the non-dimensional equations are:

$$\frac{\partial U}{\partial X} + \frac{\partial V}{\partial Y} = 0 \tag{7}$$

$$U \frac{\partial U}{\partial X} + V \frac{\partial U}{\partial Y} = -\frac{\rho_{bf}}{\rho_{nf}} \frac{\partial P}{\partial X} + Pr \left(\frac{\rho_{bf}}{\rho_{nf}} \right) \left(\frac{\partial^2 U}{\partial X^2} + \frac{\partial^2 U}{\partial Y^2} \right) \tag{8}$$

$$U \frac{\partial V}{\partial X} + V \frac{\partial V}{\partial Y} = -\frac{\rho_{bf}}{\rho_{nf}} \frac{\partial P}{\partial Y} + Pr \left(\frac{\rho_{bf}}{\rho_{nf}} \right) \left(\frac{\partial^2 V}{\partial X^2} + \frac{\partial^2 V}{\partial Y^2} \right) + \frac{(\rho\beta)_{nf}}{\rho_{nf} \beta_{bf}} Ra Pr \theta - \frac{\rho_{bf}}{\rho_{nf}} \frac{\sigma_{nf}}{\sigma_{bf}} Ha^2 Pr V \tag{9}$$

$$U \frac{\partial \theta}{\partial X} + V \frac{\partial \theta}{\partial Y} = \left(\frac{\alpha_{nf}}{\alpha_{bf}} \right) \left(\frac{\partial^2 \theta}{\partial X^2} + \frac{\partial^2 \theta}{\partial Y^2} \right) \tag{10}$$

Dimensionless boundary conditions are:

on horizontal wall: $U = 0, V = 0, \theta = 1$ (11a)

on perpendicular wall: $U = 0, V = 0, \theta = 0$ (11b)

on inclined wall: $U = 0, V = 0, \frac{\partial \theta}{\partial X} = 0$ (11c)

Local Nusselt number is defined towards horizontal hot wall of the cavity as

$$Nu_L = \frac{Lq_w}{k_{bf} (T_h - T_c)}, \text{ where } q_w = -k_{nf} \left(\frac{\partial T}{\partial x} \right)_{x=0} \tag{12}$$

Average Nusselt number on horizontal hot side can be calculated:

$$Nu_{av} = - \left(\frac{k_{nf}}{k_{bf}} \right) \int_0^1 \frac{\partial \theta}{\partial X} dY \tag{13}$$

COMPUTATIONAL PROCEDURE:

Governing dimensionless equations (7)-(10) including boundary conditions (11a)-(11c) are concluded numerically by using finite element technique of Galerkin weighted residual type that is very powerful tool to solve these kinds of nonlinear equations. This method is expressly explained by Zienkiewicz and Taylor (1991). The computational procedure for the present problem is accomplished using excellent PDEs solver Comsol Multi physics. For grid independent solution, a comprehensive mesh testing technique is calculated to guarantee the numerical solution when $Ra = 10^4$.

The subsequent five variant distinct grids designated as normal, fine, finer, extra fine, and extremely fine including of 1187, 1757, 5067, 13333 and 16773 elements in resolution field respectively. Average Nusselt number is considered for checking the grid delicacy for the aforementioned elements. **Table 2** displays that average Nusselt number for 13333 elements exhibits less difference form compared to other elements. Consequently, grid size of 13333 elements is considered of the grid independent solution.

Table 2: Susceptibility of grid for $Cu - H_2O$ nanofluid when $Ra = 10^4$.

Nodes	644	938	2666	6914	8643
Elements	1187	1757	5067	13333	16773
Nu_{av}	4.2766	4.2776	4.2856	4.2916	4.2916

We have compared our outcomes (bottom row) using streamline contours (left column) and isotherm contours (right column) along Yesiloz *et al.* (2013) (top row) for checking the validity of the present numerical scheme when $Ra = 10^4$ in **Fig 2**. The results show a strong agreement and gives us the confidence for using the current numerical scheme.

Code Validation:




Fig 2: Comparison between present study (bottom) and Aydin and Yesiloz (2011) (top) when $Ra = 10^4$.

RESULT AND DISCUSSION:

The convectonal temperature and fluid flow using $Cu-H_2O$ nanofluids within right angled triangle shape enclosure is researched numerically by Galerkin weighted residual finite element method.

The numerical results is presented and discussed for the parameters like the Rayleigh number (Ra), Hartmann number (Ha) and the volume fraction by the nanoparticles (ϕ) using isotherms contours streamline contours and average Nusselt number.

Impact of Rayleigh Number:

Fig 3(a) demonstrates impact for Rayleigh number ($Ra = 10^4, 10^5, 10^6, 10^7$) on streamline contours when $\phi = 0.04$, $Ha = 10$. This figures illustrate that for low Ra , ($Ra = 10^4$), the streamlines are not comprehensively affected by the particles of the nanofluid though horizontal wall is heated uniform. This is a good indication of strong conduction. As Rayleigh number increases ($Ra \geq 10^5$) fluid within the enclosure becomes more decomposed on account of temperature flow in that region quickly by convection. In addition, for the increase of Ra , compactness of streamline contours as well vortex strength within cavity enhances on account of predominance of free convection. Hence, convection is the dominant type of temperature flow for higher Ra . **Fig 3(b)** depicts the impact for Rayleigh number ($Ra = 10^4, 10^5, 10^6, 10^7$) on isotherm contours when $\phi = 0.04$, $Ha = 10$. This figure displays that the streamlines are not superfluously impact within cavity for low Rayleigh number which announces that conduction is the original mode of temperature flow. As Rayleigh number improves ($Ra \geq 10^5$), denseness of the isothermal contours at the center within cavity decreases. This figure also show that the isothermal contours get close to each other and also collateral to each other and closely packed neighbor horizontal warmed as well as perpendicular cold walls as a result of the dominance of the free convection. Consequently, the temperature transfer value is enhanced with the increase of Rayleigh number (Ra) caused by the potential convection mode.

Impact of Hartmann Number

Fig 4(a) depicts the results of the Hartmann number ($Ha = 0, 10, 50, 100$) on streamline contours when $\phi = 0.04$, and $Ra = 10^5$. **Fig 4(a)** shows that the flow circulations are nearly total place within the enclosure as well as develop a clockwise rotational chamber for low Hartmann number ($Ha = 0$).




Fig 3(a): Results of Ra on streamlines when $\phi = 0.04$, and $Ha = 10$.




Fig 3(b): Results of Ra on isotherms when $\phi = 0.04$ and $Ha = 10$.




Fig 4(a): Effect of Ha on streamlines when $\phi = 0.04$, and $Ra = 10^5$.






Fig 4(b): Effect of Ha on isotherms when $\phi = 0.04$, and $Ra = 10^5$.




(a)




(b)

Fig 5: Local Nusselt number for (a) Rayleigh number, and (b) Hartmann number on horizontal heated wall.

Without external magnetic impact ($Ha = 0$), the adjacent fluid near the horizontal heated wall takes heat and these heated particles moves upwards on account of buoyant force whilst comparatively refrigerant liquid neighbor cold wall access to horizontal warmed wall consequently a smooth large circulation cell is created entire the cavity. As Ha increases (> 0), the streamline patterns are changed and circulations power within the cavity decreases significantly. Because the external strong magnetic field generates Lorentz force inside the enclosure



(a)



(b)

Fig 6: Average Nusselt number for (a) Rayleigh number, and (b) nanoparticles volume fraction against Hartmann number.

that have a character of opposing of its propagation which weakens the streams within the enclosure.

Fig 4(b) demonstrate Hartmann number ($Ha = 0, 10, 20, 50$) influence on isotherms for fixed $\phi = 0.04$ and $Ra = 10^5$. These figures illustrate that the isotherms patter are more and more pronounced for the low Hartmann number ($Ha = 0$) which indicates the strong convection happens for non-appearance of magnetic field. Isothermal strength decreases and less pronounce for increase of Ha . Because potential Lorentz force is produced from Hartmann number which reduce the temperature distribution.

Therefore, Magnetic field can be used for controlling the flow domain as well as temperature transfer rate within enclosure.

Impact of Nusselt number:

Fig 5 demonstrates influence of Local Nusselt number using (a) Rayleigh number (Ra) and (b) Hartmann number (Ha) on horizontal heated wall. These figures represents, local Nusselt number increases for augmentation Ra and diminishes for the enhancement of Ha . These figures also represents that average temperature transfer value remains constant for low Ra ($=0$) which indicates that conduction is the principal mode of temperature flow. **Fig 6** depicts outcomes of Nu_{av} of (a) Rayleigh number (Ra) against Ha , and (b) nanoparticles volume fraction (ϕ) against Ha on horizontal warmed wall. These figure narrate that Nu_{av} increases with the increase of both Ra and ϕ

Whereas diminishes for augmentation of Ha . The strong buoyancy force and external magnetic field change temperature transfer value significantly. Also, additional nanoparticles into the base fluid enhances remarkably temperature transfer value. This figures also show that the average rate of temperature flow remains constant for low Ra ($=10^4$).

CONCLUSION:

We have investigated numerically free convectional flow as well as temperature flow of a right-angled triangle charged by copper-water nanofluid considering with the help of Galerkin weighted residual finite element analysis. The influence of various parameter are presented using streamline contours, isotherm contours, and Nusselt number and interpreted. The following main findings are listed:

- i. Rayleigh number play significant roll on flow field and temperature transfer value.
- ii. The fluid flow enhances for rising Rayleigh number whereas diminishes for rising Hartmann number.

- iii. Low Hartmann number and higher Rayleigh number conform better temperature transfer value.
- iv. Additional nanoparticles significantly improves temperature flow.
- v. Average Nusselt number augments for upper Rayleigh number whereas diminishes for rising Hartmann number.

NOMENCLATURE

B_0	magnitude of magnetic field
c_p	specific heat at constant pressure
g	gravitational acceleration
Ha	Hartmann number
k	thermal conductivity
L	length of the enclosure
N_{av}	average Nusselt number
P	dimensional pressure
P	dimensionless pressure
Pr	Prandtl number
Ra	Rayleigh number
T	fluid temperature
u, v	velocity component
U, V	dimensionless velocity component
x, y	coordinates
X, Y	Dimension less horizontal coordinate

Greek symbols

α	thermal diffusivity
β	thermal expansion coefficient
ϕ	solid volume fraction
μ	dynamic viscosity
ν	kinematic viscosity
θ	non-dimensional temperature
ρ	density
σ	electric conductivity
ψ	stream function

Subscript

h	heat surface
c	cold surface
nf	nanofluid
s	nanoparticle
bf	Base fluid

ACKNOWLEDGEMENT:

The author is very grateful to the editor and reviewers.

CONFLICT OF INTERESTS:

The authors declare no conflict of interest.

REFERENCES:

1. Abu-Nada, E., and Oztop H., (2009). Effects of inclination angle on natural convection in enclosures filled with Cu-water nanofluid. *Int. J. Heat fluid Flow*, **30**, 669-678. <https://doi.org/10.1016/j.ijheatfluidflow.2009.02.001>
2. Arani A., Mahmoodi M., and Amini M., (2011). Free convection in a nanofluid filled square cavity with horizontal heated plate. *Defect und Diffusion Forum*, 312-315, 433-438. <https://doi.org/10.4028/www.scientific.net/DDF.312-315.433>
3. Aydin O., and Yesiloz G., (2011). Natural convection in a quadrantal cavity heated and cooled on adjacent walls. *ASME J. Heat Transfer*, **133**(5), 1-7. <https://doi.org/10.1115/1.4003044>
4. Basak T., Roy S., Babu S.K., and Balakrishnan A.R., (2008). Finite element analysis of natural convection flow in an isosceles triangular enclosure due to uniform and non-uniform heating at the side walls. *Int. J. Heat Mass Transfer*, **51**(17-18), 4496-4506. <https://doi.org/10.1016/j.ijheatmasstransfer.2007.12.018>
5. Bhardwaj S., and Dalal A., (2013). Analysis of natural convection heat transfer and entropy generation inside right-angled triangular enclosure. *Int. J. Heat Mass tran.*, **65**, 500-513. <https://doi.org/10.1016/j.ijheatmasstransfer.2013.06.020>
6. Boulahia Z., Wakif A., and Sehaqui R., (2016). Numerical investigation of mixed convection heat transfer of nanofluid in a lid-driven square cavity with three triangular heating blocks. *International Journal of Computer Applications*, **143**(6), 0975-8887. <https://doi.org/10.5120/ijca2016910227>
7. Choi S.U.S., and Eastman J.A. (1995). Enhancing thermal conductivity of fluids with nanoparticles. *Int. Mech. Eng. Cong. and Expo*, ASME, San Francisco, USA. 196515.
8. Ece M.C., and E. Buyuk, (2006). Natural convection flow under a magnetic field in an inclined rectangular enclosure heated and cooled on adjacent walls. *Fluid Dynamics. Res.*, **38**, 564-590. <https://doi.org/10.1016/j.fluiddyn.2006.04.002>
9. Ghasemi B., and Aminossadati S.M., (2009). Natural convection heat transfer in an inclined enclosure filled with a water-Cuo nanofluid. *Numer. Heat Transfer A*, **55**, 807-823. <https://doi.org/10.1080/10407780902864623>
10. Islam S, Islam MS, and Mandal S. (2020). One dimensional heat transfer through a uniform plane wall by using finite volume method, *Aust. J. Eng. Innov. Technol.*, **2**(2), 24-30. <https://doi.org/10.34104/ajeit.020.024030>
11. Kamiyo O.M., Angeli D., Barozzi G.S., Collins M.W., Olunloyo V.O.S., and Talabi S.O.A., (2010). Comprehensive review of natural convection in triangular enclosures. *Applied Mech. Rev.*, **63**, 060801-13. <https://doi.org/10.1115/1.4004290>
12. Manca O., Jaluria Y., and Poulikakos D. (2010). Heat transfer in nanofluids. *Advances in Mech. Eng. Art. ID 380826*, **2010**, Pp. 1-2. <https://doi.org/10.1155/2010/380826>
13. Oztop H.F., and Abu-Nada E. (2008). Numerical study of natural convection in partially heated rectangular enclosures filled with nanofluids, *Int. J. Heat F. Flow*, **29**, 1326-1336. <https://doi.org/10.1016/j.ijheatfluidflow.2008.04.009>
14. Rahman M.M., Alim M.A., and Mamun M.A.H., (2009). Finite element analysis of mixed convection in a rectangular cavity

- with a heat conducting horizontal circular cylinder. *Nonlinear Anal. Model. Control*, **14**(2), 217-247.
<https://www.journals.vu.lt/nonlinear-analysis/article/view/14522/13451>
15. Rahman M.M., Alam M.S, Al-Salti N., and Eltayeb I.A. (2016). Hydromagnetic natural convective heat transfer flow in an isosceles triangular cavity filled with nanofluid using two component nonhomogeneous model. *Int. J. of Thermal Sciences*, **107**, 272-288.
<https://doi.org/10.1016/j.ijthermalsci.2016.04.009>
 16. Rashmi W., Ismail A.F., Khalid M., and Faridah Y. (2011). CFD studies on natural convection heat transfer of Al₂O₃-water nanofluids. *Heat Mass Transfer*, **47**, 1301-1310.
<https://doi.org/10.1007/s00231-011-0792-x>
 17. Sheikholeslami M., Bandpy M.G., Ellahi R., and Zeeshan A. (2014). Simulation of MHD CuO-water nanofluid flow and convective heat transfer considering Lorentz forces. *J Magn. Magn. Mater.*, 369, 69-80.
<https://doi.org/10.1016/j.jmmm.2014.06.017>
 18. Yesiloz G., and Aydin O. (2013). Laminar natural convection in right-angled triangular enclosures heated and cooled on adjacent walls. *International Journal of Heat and Mass Transfer*, **60**, 365-374.
<https://doi.org/10.1016/j.ijheatmasstransfer.2013.01.009>
 19. Uddin M.J., and Hoque A.F., (2018). Convective heat transfer flow of nanofluid in an isosceles triangular shaped enclosure with an uneven bottom wall. *Chemical Engineering Transactions*, **66**, 403-408.
<https://doi.org/10.3303/CET1866068>
 20. Varol Y., Oztop H.F., and Yilmaz T., (2007). Natural convection in triangular enclosures with protruding isothermal heater. *Int. J. Heat Mass Transfer*, **50**(13-14), 2451-2462.
<https://doi.org/10.1016/j.ijheatmasstransfer.2006.12.027>
 21. Zienkiewicz O.C., and Taylor R.L., (1991). The finite element method. 4th ed. *McGraw-Hill*.
<https://trove.nla.gov.au/version/40313901>

Citation: Islam T., Akter N. and Jahan N. (2020). MHD free convective heat transfer in a triangular enclosure filled with Copper-water nanofluid, *Int. J. Mat. Math. Sci.*, **2**(2), 29-38.

<https://doi.org/10.34104/ijmms.020.029038> 